



Main features:

1. Model:M12

2. 8-channel microphone input, 4-channel (two groups) stereo input;
3. 48V phantom power
4. Two auxiliary output, an AUX send, an FX send, aux sent to the flipper before the signal, FX sent to the Flipper after the signal, the signal sent by the knob control;
5. Each input Channel with the PFL key, easy to listen to the flipper before the signal
6. L-R switch (main output switch) and G1-G2 switch (two group switches)
7. USB display function with LED, can display song name and lyrics, support MP3, WAV and other formats,
8. with Bluetooth function, you can directly bluetooth input audio
9. with U disk recording function;
10. can connect to the computer, through the sound card input and output audio to the computer;
11. built-in effector
12. Microphone input can choose a speakon or 6.35 connector, stereo input can choose RCA OR 6.35 connector

SPECIFICATION :

- 1、 Frequency response : 20Hz~20KHz(+/-0.5dB) ;
- 2、 THD : <1%(20HZ-20KHZ) ;
- 3、 Noise : $\leq -110\text{dBm}$
- 4、 EQ:
 - LF : 80Hz/ $\pm 15\text{dB}$;
 - MF : 2.5KHz $\pm 15\text{dB}$;
 - HF : 12KHz/ $\pm 15\text{dB}$;
- 5、 Max gain(line input) : $\geq 20\text{dB}$;
- 6、 Max gain(IMic input) : $\geq 50\text{dB}$;
- 7、 Input Impedances :
 - Mic in : $\geq 1.0\text{K}\Omega$;
 - Line output : $\geq 10\text{K}\Omega$;
 - All other return input:20 K Ω ;
- 8、 Output Impedances :
 - Left output : $\leq 300\Omega$;
 - Right output : $\leq 300\Omega$;
 - All other output : $\leq 10\text{K}\Omega$;
- 9、 Power : $\leq 40\text{W}$;
- 10、 Input AC : AC220V 50Hz ;
- 11、 SIZE(machine) : (H*W*D) 90x445x410 mm ;
- 12、 Size(package) : (H*W*D) 195*510*485 mm ;
- 13、 N.W : 5.1Kg
- 14、 G.W : 7.6Kg