



MLA115B MAseries MLA115BAS

Line Array System

The **MLA115B** is a single 15" low frequency enclosure designed for sub-bass reinforcement to **MLA206**, made of high quality plywood with polyurea waterproof paint. All rigging parts are made of aluminium alloy. The **MLA115BAS** is equipped with SA2.68 digital amplifier module based on **MLA115B** to be an active system to push 4pcs **MLA206**.

FEATURES

- High quality plywood with polyurea waterproof paint
- Direct radiating design
- High temperature 4"(100mm) voice coil

MLA115B是一款单15"超低音箱。采用一只15" 100芯低音单元，直射式结构设计，吊挂系统采用铝合金材质，与**MLA206**配合，可吊挂、可堆码，以提升系统低频表现，箱体采用多层复合夹板，聚脲喷涂。**MLA115BAS**是在**MLA115B**基础上配置SA2.68功放组件成为系统，与**MLA206**配合使用。




系统特征

- 高质量单元配置，高强度夹板箱体
- 直射式设计，低音丰富自然
- 超长品质保证期：品质与信心的保证

CONFIGURATION

适用范围

- 配合**MLA206**线性阵列系统，增加低音表现
- 中小型流动演出
- 多功能厅、高级酒店会所



MODEL

FREQUENCY RESPONSE(-3dB)

DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

MLA115B

40Hz-300Hz

1×15"(385mm)/4"voice coil LF

600W RMS,2400W peak

99dB 1watt/1meter

127dB continuous,133dB peak

8 ohms nominal

2×Speakon NL4

772mm×572mm×540mm

35 kg/pc

38 kg/pc

MLA115BAS

35Hz-300Hz and 50Hz-20kHz

1×15"(385mm)/4"voice coil LF

900W/4Ω+1200W/4Ω

--

127dB continuous,133dB peak

--

INPUT TYPE:Balanced Differential line

772mm×572mm×540mm

37 kg/pc

40 kg/pc