



MRseries MR12C MR12CA

Two-way Loudspeaker System

FEATURES

- High quality plywood with polyurea waterproof paint
- Neodymium HF driver
- Compact two-way passive system
- Patent 90° × 40° horn

产品特点

- 高质量单元配置，高强度夹板箱体
- 超长品质保证期：品质与信心的保证

适用范围



- 多功能厅、高级酒店会所
- 流动商演、乐队扩声以及舞台返送音箱

The MR12C is a high precision and high power stage monitor, made of high quality plywood with polyurea paint. It offers a "studio monitoring" type of response, exceptional dynamic capability and very low distortion. Fitted with one 12" woofer and one 1" exit neodymium compression driver coupled to a patent 90° × 40° horn. MR12CA is equipped with FA1.6 digital amplifier module based on MR12C to be an active monitor.

MR12C是一款12寸同轴两分音全音域舞台监听音箱，采用一只12寸高效率中低音单元和一只1寸喉口44芯强磁驱动器，配置专门设计的90° × 40° 号角。箱体采用多层复合夹板，聚脲喷涂制作。MR12CA是在MR12C的基础上配置FA1.6功放组件成为有源音箱。



CONFIGURATION



MODEL

FREQUENCY RESPONSE(-3dB)

FREQUENCY RESPONSE(-10dB)

DRIVERS

RATED POWER

SENSITIVITY

MAXIMUM SPL

IMPEDANCE

DISPERSION(-6dB)

CROSSOVER FREQUENCIES

INPUT CONNECTORS

PACKAGE SIZE

NET WEIGHT

GROSS WEIGHT

MR12C

55Hz-18kHz

50Hz-20kHz

1 × 12"(300mm)/3"voice coil LF

1 × 1"(25mm)/1.7"voice coil HF

300W RMS,1200W peak

97dB 1watt/1 metre

122dB continuous,128dB peak

8 ohms nominal

90° × 40°

2.3kHz passive

2 × Speakon NL4

547mm × 420mm × 595mm

21 kg/pc

24 kg/pc

MR12CA

55Hz-18kHz

50Hz-20kHz

1 × 12"(300mm)/3"voice coil LF

1 × 1"(25mm) / 1.7"voice coil HF

600W/8Ω

--

122dB continuous,128dB peak

--

90° × 40°

--

INPUT TYPE: Balanced Differential line

547mm × 420mm × 595mm

23 kg/pc

26 kg/pc