



MRseries MR12N

Two-way Loudspeaker System

FEATURES

- High quality plywood with polyurea waterproof paint
- Neodymium HF driver
- Compact two-way passive system
- Patent 90° × 40° hron

The MR12N is a high precision and high power stage monitor. It offers a "studio monitoring" type of response, exceptional dynamic capability, very low distortion, and has mechanical system for angle adjustment when floor mounted.

MR12N是一款12"同轴两分音全音域监听音箱。采用一只12"强磁同轴单元, 90°×40°恒指向性号角,箱体采用多层复合夹板,聚脲弹性防水喷涂制作。


产品特征


- ●高质量单元配置,高强度夹板箱体
- ●多角度设计适合不同舞台
- ●超长品质保证期: 品质与信心的保证

适用范围

- ●多功能厅、高级酒店会所
- ●流动商演、乐队扩声以及舞台返送音箱

CONFIGURATION





FREQUENCY RESPONSE(-3dB) 55 Hz-18kHz FREQUENCY RESPONSE(-10dB) 50 Hz-20kHz

DRIVERS 1×12"(300mm)/3"voice coil LF

 1×1.4 "(36mm)/3"voice coil HF

RATED POWER 300W RMS,1200W peak SENSITIVITY 97dB 1watt/1 metre

MAXIMUM SPL 122dB continuous,128 dB peak

IMPEDANCE 8 ohms nominal

DISPERSION(-6dB) 90°×40°

CROSSOVER FREQUENCIES 1.5kHz passive INPUT CONNECTORS 2× Speakon NL4

PACKAGE SIZE 495mm×465mm×643mm

NET WEIGHT 17 kg/pc GROSS WEIGHT 20 kg/pc

